

Isofield Beta Kits

Sterile Cleanroom coverall with mandarin collar, hood with integrated facemask & overboots

PRODUCT INFO



MANDARIN COLLAR COVERALL

Two-layer mandarin collar provides secure fit at neck area
Zip flap with double-sided tape prevents ingress and egress of particles

Low-linting, anti-static fabric suitable for chemo handling

Elasticated thumb loops

Back elastic to prevent bellows effect



HOOD WITH INTEGRATED FACEMASK

Integrated mask with two ties for quick and easy donning

Latex-free enclosed elastic face opening for comfort fit

Extra-long yoke for added protection



OVERBOOTS

Extra long — 50cm knee height
Two ties for added security
Anti-slip PU sole



QUALITY ASSURANCE

Type 5/6 certified

Manufactured in a facility operating under ISO 9001:2015 quality management system

Processed in a NEBB certified ISO Class 5 cleanroom

STORAGE & SHELF LIFE

Store in a dry, cool place (<40°C) away from direct sunlight

Do not expose open cartons to prolonged direct fluorescent light

Five (5) years from date of manufacture

CLEANROOM COMPATIBILITY

GMP Grade A cleanroom
GMP Grade B cleanroom

ISO Class 4 cleanroom
ISO Class 5 cleanroom

Class 10 cleanroom
Class 100 cleanroom

APPLICATIONS

Pharmaceutical product preparation

Cleanroom cleaning and preparation

Aseptic filling & labelling

Medical device manufacturing

Handling of active materials

Blending operations for biotechnologies

Handling chemotherapy in hospital pharmacy


PACKAGING

1 set (hood/coverall/boots) per sealed inner bag,

1 inner bag per sealed outer bag,

40 outer bags per carton liner with twist tie (XS-2XL),

35 outer bags per carton liner with twist tie (3XL-4XL)

 Three items are aseptically folded

PRODUCT CODE

REF

80451

XSMALL	80451XS	XLARGE	80451XL
SMALL	80451S	XXLARGE	80451XXL
MEDIUM	80451M	3XLARGE	80451XXXL
LARGE	80451L	4XLARGE	80451XXXXL



STERILE R

MATERIAL PERFORMANCE PARAMETERS

DESCRIPTION	UNITS	METHOD	SPECIFICATION	TYPICAL
Basic weight PP/PE film laminate	g/m ²	ISO 9073-1-1989	±2	60
Hydrostatic head	mmH ₂ O	ISO 811-1981	≥100	213
Air permeability	l/m ² /S	GB/T5453	≥	2000
Surface resistivity	Ω / sq	ASTM D257	Static dissipative	10 ¹⁰
Overboot slip resistance	Coefficient of Friction (COF)	ASTM D1894	≥0.5	0.6 (Static) 0.5 (Dynamic)

HELMKE DRUM TEST RESULT CLASS 1

PARTICLE SIZE	CUMULATIVE RELEASE RATE (COUNTS/MIN)	SPECIFICATION	CLASS	TEST METHOD
≥ 0.3µm	743*	Less than 2,000	1	IEST-RP-CC003.4
≥ 0.5µm	318*	2,000 - 20,000	1	IEST-RP-CC003.4
≥ 5.0µm	43*	20,000 - 200,000	1	IEST-RP-CC003.4

*Test carried out on coverall and hood. Typical results.

PERMEATION TEST AGAINST CHEMO DRUGS

CHEMOTHERAPY DRUGS	BREAKTHROUGH TIME	TEST METHOD
Carmustine	30 min	ASTM F739-20
Cisplatin	> 480 min	ASTM F739-20
Cyclophosphamide	> 480 min	ASTM F739-20
Doxorubicin HCl	> 480 min	ASTM F739-20
Etoposide	> 480 min	ASTM F739-20
Fluorouracil	> 480 min	ASTM F739-20
Methotrexate	> 480 min	ASTM F739-20
Paclitaxel	> 480 min	ASTM F739-20
Thiotepa	60 min	ASTM F739-20

*Results achieved under controlled laboratory conditions, by accredited ISO 17025 third party testing laboratory

**Mask not tested

TECHNICAL PROPERTIES

TEST REFERENCE	EXPLANATION	TEST RESULTS
EN 14325:2004 EN ISO 6530:2005	Repellency to chemicals	10% Sodium hydroxide Level 3
		30% Sulphuric acid Level 3
		O-Xylene Level 2
		Butan-1-ol Level 2
		70% Isopropyl alcohol Level 2
		70% Ethanol Level 2
EN 14325:2004 EN ISO 6530:2005	Resistance to penetration by chemicals	10% Sodium hydroxide Level 3
		30% Sulphuric acid Level 3
		O-Xylene Level 3
		Butan-1-ol Level 3
		70% Isopropyl alcohol Level 3
		70% Ethanol Level 3
EN 14325:2004 EN ISO 9073-4:1997	Trapezoidal tear resistance	Machine direction Class 2
		Cross direction Class 2
EN 14325:2004 EN ISO 13934-1:2013	Tensile strength	Machine direction Class 1
		Cross direction Class 2
EN ISO 13982- 2:2004 EN ISO 13982- 1:2004 (Type 5)	Inward leakage of aerosols and fine particles into suits	Pass
	IL _{82/90}	0.544%
	IL _{8/10}	0.233%
EN 14325:2004 EN ISO 12947-2:2016	Abrasion resistance	Class 2
EN 14325:2004 EN ISO 7854:1997, Method B	Flex cracking resistance	Class 6
EN 14325:2004 EN 863:1995	Puncture resistance	Class 1
EN 14325:2004 [5.5]	Seam strength	Class 2
EN 13034:2015 + A1:2009 ISO 17491-4:2008 (Type 6)	Resistance to penetration by a spray of liquid (Spray Test)	Pass
In-house AQL 1.5	Test plan for major defect	Pass
EN ISO11137 Part 2:2015	Sterility validation	SAL 10 ⁻⁶



Hood with Integrated Tie-on Facemask

FACEMASK MATERIALS

Outer layer	Non-woven spunbond polyester
Filtration Layer	Non-woven meltblown polyester
Inner facing layer	Non-woven polypropylene / polyethylene
Tie-tapes	Non-woven polyester

FACEMASK FILTRATION PROPERTIES

Particle Filtration Efficiency (PFE) @ 0.1 Micron	94%
Bacterial Filtration Efficiency (BFE) @ 0.3 Micron	97%
Differential Pressure (ΔP), mm H ₂ O/cm ²	6.8

LOADING

	EURO-PALLET	STANDARD PALLET
Pallet size	W80 L120cm	W100 L120cm
Gross weight	13.31 - 16.76kg	13.31 - 16.76kg
Carton size	W38 L58 H47cm	W38 L58 H47cm
Nett weight	10.51 - 13.96kg	10.51 - 13.96kg
Air freight pallet	Max height: 109cm Layers: 2 Cartons: 8	Max height: 109cm Layers: 2 Cartons: 10
Sea freight pallet	Max height: 156cm Layers: 3 Cartons: 12	Max height: 156cm Layers: 3 Cartons: 15

DOCUMENTATION



CERTIFICATE OF CONFORMANCE (COC)
CERTIFICATE OF ANALYSIS (COA)
CERTIFICATE OF PROCESSING (COP)

Please [email us](#)



FACTORY RELATED CERTIFICATIONS
To request ISO9001 Certificate,
please [email us](#)

Country of origin: **China**
HS Code: 6210109000

This data sheet and any other claims made by or on behalf of Isofield shall not be taken as a warranty of merchantability or as a statement that any Isofield products are suitable for a specific purpose. Isofield shall not be held responsible for the end user's choice of product for a particular application.



EUROPE

ISOFIELD (IRELAND) LTD
70 Northumberland Road, Ballsbridge Dublin 4,
Ireland T +44 (0) 1638 6762 39

ASIA

ISOFIELD SDN BHD
6 Jalan Gudang 16/9, Seksyen 16, 40200, Shah Alam,
Selangor, Malaysia, T +603 5512 1709

CONTACT

www.isofield.com
info@isofield.com