



**uzhou Myesd Ultra Clean Technology Co. LTD**  
**Sticky Mat Specifications**

Issue number	MSD/QI-QS-354	
Versions	A0	
Issuing date	20240325	
Approval	Review	Compilation
Ruanqiuying	Qianmaqun	Shanlili

**Basic Information**

1	Product Name	Sticky Mat
2	Specifications	Blue, 4C
3	Main Materials	Low-density polyethylene (LDPE)
4	Appearance	No deformation, smooth and flat surface without noticeable particles, uniform color with no noticeable color variation
5	Glue Ingredients	White glue-linked acrylic emulsion, free of heavy metals and active chemical ingredients, no pungent odor
6	Applying Condition	Glossy and uniform finish, no flaking
7	Single-Sided Adhesion (g/25mm)	High viscosity: 800g

**size**

NO.	Item	Unit	Technical indicators
1	Dimensions	inch	24"*36"±5%
2	Thickness	mm	0.04±0.005

**Material properties**

NO.	Properties	Unit	Technical indicators
1	Mandatory tensile strength	MPA	≥10
2	Transverse tensile strength	MPA	≥8
3	Mandatory elongation at break	%	≥150
4	Transverse elongation at break	%	≥200

**Features**

1. The sticky mat is made of multiple layers of polyethylene film. To use, simply peel off the protective layer from the back, apply it to the floor, press it firmly against the surface, and then peel off the protective layer from the front.
2. If a large amount of dust collects during use, cleaning is not necessary; simply peel off the film and use a new one.
3. The sticky mat can be used alone or with a frame. The bottom pad can be removed without leaving any residue or causing any environmental pollution.

**Scope of application**

It is mainly used at the entrance and buffer zone of clean spaces. It can remove dust from soles of shoes or wheels and keep the environment clean.